


Photoelectrics Amplifier, μ -Processor Controlled Type S1430, 3 Inputs/3 Outputs

CARLO GAVAZZI



- μ -Processor controlled
- Amplifier unit for 3 sets of photoelectrics
- 3 independent outputs
- NPN/PNP both NO or NC selectable
- Self-diagnostic functions
- Alignment failure indication
- Multivoltage 12 to 30 VAC/DC
- Modulated and synchronized light
- Adjustable sensitivity for each channel
- LED indications: supply, outputs, signal quality
- 11-pin plug-in housing
- For 115 or 230 VAC use power supplies S1430 PWS115 or S1430 PWS230

Product Description

μ -Processor controlled amplifier for 3 sets of photoelectric sensors, type MOFTR, MKFTR, MIFTR or MHFTR. Utilising an 11-pin circular plug for easy connection, outputs freely selectable for NPN/PNP or NO/NC. Self-

diagnostics for system test. Protected against short-circuits, reverse wiring or cross talk from adjacent photoelectrics. Multi-voltage power supply. Sensitivity is individually adjustable for each set of photoelectrics.

Ordering Key S14 30 UAP 912

Type _____
 Special function _____
 Output type _____
 Power supply _____

Type Selection

Plug type	Ordering no. Supply: 12 - 30 VAC/DC	Ordering no. Supply: 115 VAC	Ordering no. Supply: 230 VAC
Circular, 11 pins	S 1430 UAP 912	S 1430 PWS 115 Power Supply for S 1430 UAP 912	S 1430 PWS 230 Power Supply for S 1430 UAP 912

Specifications

Rated operational voltage U_b pins 2 & 10	DC 10.8 to 33 VDC AC 10.8 to 33 VAC, 45 to 65 Hz
Rated operational power	AC supply 4 VA DC supply 3 W
Power ON delay (t_r)	< 300 ms
Output function	NPN and PNP switching Make and break function DIP-switch selectable
Output current	Continuous (I_o) 100 mA per output Short-time (I) 100 mA max.
Min. load current (I_m)	0.5 mA
OFF-state current (I_r)	Max. 100 μ A
Voltage drop (U_d)	\leq 3.5 VDC
Protection, outputs	Reverse polarity, short-circuit, transients
Supply to photoelectric switch	
Emitter	Tx1: Pin 1 Tx2: Pin 9 Tx3: Pin 6 Shield: Pin 11 (common)
Supply voltage (open loop)	7 V square wave

Current	\leq 300 mA short-circuit protected
Output resistance	10 Ω
Receiver	Rx1: Pin 4 Rx2: Pin 7 Rx3: Pin 8 Shield: Pin 5 (common)
Supply voltage (open loop)	5 VDC
Short-circuit current	10 mA
Input resistance	470 Ω
Sensitivity (% of S_n)	<ul style="list-style-type: none"> • 2 ranges, DIP-switch selectable - low sensitivity (25%) - high sensitivity (100%) • Sensitivity adjustment with 270°: Turn knob on CH 1, 2, 3 • Maximum range indicated on photoelectric switch data sheet in high sensitivity range only • Operation within low sensitivity range, increases ambient light and crosstalk immunity
Note:	



Specifications (cont.)


Operating frequency (f) Light/dark ratio 1:1	16 Hz
Response time OFF-ON (t _{ON}) ON-OFF (t _{OFF})	20 ms 20 ms
Indication Supply ON Output ON Signal quality	LED, green LED, yellow LED, red
Environment Overvoltage category Degree of protection Pollution degree	III (IEC 664) IP 20 (IEC 529, 947-1) 3 (IEC 664/664A, 947-1)
Temperature Operating Storage	-20° to +50°C (-4° to +122°F) -50° to +85°C (-58° to 185°F)
Weight	150 g

Truth Table

	Make switching			Break switching		
	Yes	No	No	Yes	No	No
Object present	Yes	No	No	Yes	No	No
Dirt on lenses, misaligned or sensitivity too low	--	No	Yes ¹⁾	--	No	Yes ¹⁾
Output LED yellow	OFF	ON	ON	OFF	ON	ON
Level LED red	OFF	OFF	ON or flashing	OFF	OFF	ON or flashing
Output NPN/PNP	OFF	ON	ON	ON	OFF	OFF

¹⁾ Under normal operating conditions, the red level indication LED has to be OFF. The level indication LED will turn on shortly each time an object enters or exits the sensing zone, even if the photoelectric switch is correctly installed and adjusted.

Operation Diagram



Dimensions

DIP-switch (located behind cover):

SW 1 2 3 4 5 6

- 1: PNP/NPN CH 1 output
- 2: PNP/NPN CH 2 output
- 3: PNP/NPN CH 3 output
- 4: Low sensitivity (25%) / high sensitivity (100%)
- 5: Test button, transmitters are transmitting, no short, wired correctly
- 6: Test button, receivers are receiving, no short, wired correctly
- 5+6 together: System test (transmitter and receiver)

<p>sw 1, 2, 3:</p> <ul style="list-style-type: none"> <input type="checkbox"/> PNP make/NPN break <input type="checkbox"/> NPN make/PNP break <p>sw 5:</p> <ul style="list-style-type: none"> <input type="checkbox"/> Transmitter test <input type="checkbox"/> Normal operation <p>sw 5+6:</p> <ul style="list-style-type: none"> <input type="checkbox"/> System test <input type="checkbox"/> Normal operation 	<p>sw 4:</p> <ul style="list-style-type: none"> <input type="checkbox"/> Range 25% <input type="checkbox"/> Range 100%, normal operation <p>sw 6:</p> <ul style="list-style-type: none"> <input type="checkbox"/> Receiver test <input type="checkbox"/> Normal operation
--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Procedure for Test Functions (Dip-switch Selection)

Transmitter test (pin 5 in the up position)

When pin 5 is placed in the up position all yellow and red LED's on the front of the unit will flash simultaneously. Once the test is completed (approx. 3 scans) and a wiring fault is detected, such as reverse polarity or short-circuit, the transmitter that has the fault condition will be indicated by the red LED being continuously ON. If a fault condition is not existing then only the yellow LED will be ON. If a fault exists, correct the fault condition and then repeat the test, this will ensure proper wiring has been done. Always reset **pin 5** for normal operation of system when testing completed.

Receiver test (pin 6 in the up position)

When pin 6 is placed in the up position all yellow and red LED's on the front of the unit will flash simultaneously. Once the test is completed (approx. 3 scans) and a wiring fault is detected, such as reverse polarity or short-circuit, the receiver that has the fault condition will be indicated by the red LED being continuously ON. If a fault condition is not existing then only the yellow LED will be ON. If a fault exists, correct the fault condition and then repeat the test, this will ensure proper wiring has been done. Always reset **pin 6** for normal operation of system when testing completed.

Function test (pin 5 and 6 in the up position)


When pin 5 and 6 are both placed in the up position (simultaneously) the yellow and red LED's on the front of the housing will begin to flash simultaneously and then the LED's will cycle from channel

1 to channel 2 and then to channel 3. Once the complete system scan is done the indication of the system condition will be displayed (see below). System test will continue until pins 5 and 6 are reset.

LED Indication

—	Yellow LED ON	}	System Test OK
△	Red LED OFF		
—	Yellow LED ON	}	Tx's and Rx's mismatched, e.g. Rx3 seeing Tx1
△	Red LED ON		
—	Yellow LED OFF	}	Alignment error or beam obstructed by object
△	Red LED ON		

Wiring Diagrams



ON sockets



- 1: Transmitter 1
- 2: Supply (+ VDC)
- 3: No connection
- 4: Receiver 1
- 5: GND (Receivers)
- 6: Transmitter 3
- 7: Receiver 2
- 8: Receiver 3
- 9: Transmitter 2
- 10: Supply (- VDC)
- 11: GND (Transmitters)

Output


- A: + (10-40 VDC)
- B: Output 1 (max. 100 mA)
- C: Output 2 (max. 100 mA)
- D: Output 3 (max. 100 mA)
- E: For handheld tester
- F: - DC

Wire colour coding

- white
- black
- red
- green
- yellow
- blue



Interface



6IODC
DIN-rail interface
(DIN EN 50 035, EN 50 022)

Power Supply



S 1430 PWS
Power supply for 12 VDC/1 A

Accessories

- 11 pole circular socket
 - Socket cover for S111
 - Socket cover for S411
 - Holding down spring
 - Mounting rack
 - Front panel mounting bezel
 - Connection cable (2 plugs)
 - 2 x 6/6 modular plugs
 - Power supply for 115 VAC
 - Power supply for 230 VAC
 - DIN-rail interface
- S111, S111A, S411, ZPD11
 - BB1
 - BB4
 - HF
 - SM13
 - FRS2
 - 2 x 6/6 mod. 2.0 m
 - S 1430 PWS 115
 - S 1430 PWS 230
 - 6IODC

Delivery Contents

- Output connection cable
 - Amplifier
 - DIN-rail interface
 - Screw driver
 - **Packaging:** cardboard box
- 1 x 6/6 mod. 1.0 m
 - S 1430 UAP 912
 - 6IODC