

Midi Industrial Relay Type RMI. 2-10 10A Monostable



RMI. 2-10 10A

- High switching power
- Small size
- Wide range of application
- 12 A switching capacity
- 2 poles configuration
- AC coils 6 to 230 VAC
- DC coils 5 to 110 VDC
- 1.5 KV dielectric coil to contacts
- Au-clad contact available
- Conform to the CE low voltage directive
- UL, VDE, CSA approved
- Standard with LED, Push with arm and Flag

Product Application

- Lift-Elevators
- Moving Stairs
- Textile machines
- Wood working machines
- Plastic molding machines
- Ceramic working machines

Ordering Key

RMI A 2-10 012 DC

Type _____
Terminal version _____
Contact code _____
Rated coil voltage _____
DC / AC _____

Terminal version: A = Soldering terminals
B = PCB terminals

Type Selection

Contact configuration	Contact rating	Contact code
2 change over contacts (DPDT {2-form C})	10 A	2-10

Coil Characteristics, DC (20°C)

Nominal voltage VDC	Pick-up voltage VDC	Drop-out voltage VDC	Coil resistance Ω
5	4.0	0.5	27.5 $\pm 10\%$
6	4.8	0.6	40.0 $\pm 10\%$
12	9.6	1.2	160.0 $\pm 10\%$
24	19.2	2.4	650.0 $\pm 10\%$
48	38.4	4.8	2600.0 $\pm 15\%$
110	88.0	11.0	11000.0 $\pm 15\%$

Coil Characteristics, AC (20°C)

Nominal voltage VAC	Pick-up voltage VAC	Drop-out voltage VAC	Coil resistance Ω
6	4.8	1.8	11.5 $\pm 10\%$
12	9.6	3.6	46.0 $\pm 10\%$
24	19.2	7.2	184.0 $\pm 10\%$
48	38.4	14.4	735.0 $\pm 10\%$
115/120	96.0	36.0	4550.0 $\pm 15\%$
230	176.0	66.0	14400.0 $\pm 15\%$

Contact Characteristics

Contact rating (with resistive load)	10 A - 250 VAC	Initial contact resistance	50 m Ω (at 1 A 6 VDC)
Usually rating	10 A - 250 VAC / 30 VDC	Voltage	
Max. rating	12 A - 250 VAC / 30 VDC	Max. switching voltage	250 VAC / 30 VDC
Material	Silver alloy	Max. switching power	300 W - 2500 VA
Current		Life	
Max. switching current	10 A	Electrical life	1x10 ⁵ ops (1800 ops/h)
		Mechanical life	1x10 ⁷ ops (18000 ops/h)


Insulation

Test Voltage (1 min.) Between coil and contacts Between open contacts	1000 VAC 1000 VAC	Between contacts sets Initial insulation resistance	1500 VAC 1.000 MΩ - 500 VAC
--	------------------------------------	--	--


General Data

Nominal coil power	0.9 W DC / 1.2 VA AC	Shock resistance	
Operating time (At nominal voltage)	25 ms	Funkcional	100 m/s²
Release time (At nominal voltage)	25 ms	Destructive	1000 m/s²
Ambient temperature	-55° C to +70° C	Humidity	35% to 95%
Vibration resistance	10 to 55 Hz 1.5 mm	Termination	PCB and AMP
		Construction	Dust cover
		Weight	~ 37 g


Dimensions



Pin View




Wiring Diagram




Diagrams

1 Electrical life reduction factor at AC inductive load



2 Maximum DC resistive load breaking capacity



Approvals



The approvals stated are not generally applicable to all the relay versions.

For further information please apply for relevant data sheets ref. **3.84.00.10.x**